

# Gateway Brush (Frontrunner Brush)



External entrance matting with heavy-duty brush inserts for maximum dirt removal.



Stop snow, ice and dirt in its tracks with Gateway Brush, an extra aggressive entrance mat designed for extreme weather conditions.

Heavy-duty brush strips scrape shoes clean, while the open grid traps and collects the debris, preventing it from being walked inside. Gateway Brush works as a standalone entrance mat, or you can pair it with a mat specifically designed for inside, like Gateway Plus.



## Features:



Diamond cut pattern



Two layer open-grid construction



Nylon brush inserts



Comes in 10m (33') rolls or modules



Made from flexible PVC



## Benefits:



Slip resistant, high soil removal



Excellent drainage



Scrapes shoes clean



Seamless installation



Easy to cut to fit on site, contours to uneven surfaces



## Plastex Matting Inc.

120 55th St NE  
Fort Payne, AL 35967  
+1 256 845 7725

USA + UK manufactured matting products:  
[plastexmatting.com](http://plastexmatting.com)

## Data sheet

### Standard sizes:

<b>Product</b>	Gateway Brush
<b>Height</b>	14 - 19mm (9/16" - 3/4")
<b>Standard roll options</b>	10 x 0.6m (33' x 2')
	10 x 0.91m (33' x 3')
	5 x 1.2m (16'6" x 4')
<b>Standard module options</b>	0.8 x 1.2m (2'7" x 4')
	1 x 1.5m (3'3" x 4'11")
	1.1 x 2m (3'7" x 6'7")
<b>Weight</b>	12.7 kg/m <sup>2</sup> (2.6 lb/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides.

### Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3mm)	Width (0+2mm)
<b>Gateway Brush</b>	14/19 mm	10 m	60 cm 91 cm
	14/19 mm	5 m	120 cm

All dimensions are nominal

### PVC grid technical information:

<b>Acoustic</b>	Excellent sound absorption
<b>Chemical</b>	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by <a href="#">downloading this information sheet</a>
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC)
<b>Environment</b>	We don't use any substances included in the SVHC list under REACH in any of our matting products.
<b>Fire</b>	EN ISO 13501-1:2007-Cfl-S2. Nylon brush fibres: UL94-V2
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <a href="#">downloading this information sheet</a> .
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>UV light</b>	Resistant to PVC degradation
<b>Warranty</b>	Two years. Visit our <a href="#">policies page</a> for more information about warranties

### Nylon brush inserts technical information:

<b>Construction</b>	Aligned tufting
<b>Bristle diameter</b>	0.3mm
<b>Insert thickness</b>	12mm
<b>Bristle content</b>	Nylon 6.6 monofilaments
<b>Bristle height</b>	4.5mm
<b>Backing</b>	PVC

## Data sheet

### Colours:



Black



Dark grey

More colours  
available  
upon request

### Installation:

Gateway Brush's one-piece construction means installation is simple:

- No special tools or previous site visits
- Fits with different well depths
- Contours to the floor

[Watch](#) or download the [recessed entrance matting installation instructions](#) and the [surface-mounted installation instructions](#).

### Cleaning:

Keeping Gateway Brush looking good is easy:


- Reduces cleaning intervals
- Simply roll or lift to clean
- No special tools needed
- Easy to clean using a vacuum, plus a coarse brush for clearing the debris in the grid

[Watch](#) or [download](#) the the cleaning instructions.

### Ancillaries:


#### > For surface mounted installations

#### PVC edging (H: 14mm, W: 60mm)



Supplied in rolls of 10.1m (33') length. One tube of cold welding paste recommended for every 10m of edging. Comes in black, dark grey, dark brown, holly green, Oxford blue, yellow. Size: 14mm x 60mm x 10.1m (9/16" x 2 1/2" x 33')

#### PVC edging (H: 14mm, W: 100mm)




Supplied in rolls of 10.1m (33') length. One tube of cold welding paste recommended for every 10m of edging. Comes in black, dark grey and yellow. Size: 14mm x 100mm x 10.1m (9/16" x 3 3/4" x 33')

#### Aluminum edging (H: 15mm)



Supplied in sections of 2m (6'6") length with fixing screws and plugs. Comes in anodized aluminum and powder coated yellow. Size: 15mm x 45mm x 2m (9/16" x 1 13/16" x 6'6")

#### PVC snap track (H: 14mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. We recommend one tube of cold welding paste for every 10m of edging. Comes in black and dark grey. Size: 14mm x 2.5m (9/16" x 8'2").

## Data sheet

### Ancillaries:

#### > For recessed installations

#### R frame (H: 14mm)



You'll need these to secure the matting on the left-to-right edges. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodized aluminum, powder coated dark grey and black. Size: 14mm x 12mm (9/16" x 15/32")

#### J frame (H: 18mm)




Installing Gateway against a wall? You'll need a J frame to secure the matting on the left-to-right edges. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in dark grey and black. Size: 18mm x 60mm (1 1/16" x 2 3/8")

#### T frame (H: 14mm)



You can use a T frame (27mm) to divide the matting into sections left-to-right – this makes it easier to lift and clean. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodized aluminum, powder coated dark grey and black

#### TL frame (H: 14mm)




You can use a T/L frame (55mm) to divide the matting into sections left-to-right – this makes it easier to lift and clean. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodized aluminum

#### H section (H: 14mm)



If the front-to-back dimension of the mat well is greater than the final width of your matting, you may need a H section to secure the different sections together. Supplied in sections of 3m (10') length, with fixing screws and plugs. Comes in black, with mat insert colour specified. Size: 14mm x 13mm (9/16 x 1/2")

#### U section (H: 14mm)



If the front-to-back dimension of the mat well is greater than the final width of your matting, you may need a U section to secure the different sections together. Supplied in sections of 3m (10') length, with fixing screws and plugs. Comes in anodized aluminum, powder coated dark grey and black. Size: 14mm x 19mm (9/16" x 3/4")

#### L frame (H: 15mm)



Installing around a circular door or non rectangular space? You'll need a L frame to secure the matting. Size: 15mm x 2.7m length (5/8" x 8')